



Isopropyl Fuel De-Icer

Premium Gas Line Antifreeze

Description

Nemco Isopropyl Fuel De-Icer contains 99% pure isopropyl alcohol and is designed to improve engine performance by eliminating moisture and ice from fuel systems. This assures better starting in cold and wet conditions and helps to keep carburetors, injectors, and fuel systems clean and free of ice and moisture. It can be used with all grades of gasoline and diesel fuel. This product can be used when storing vehicles to help remove moisture from fuel tanks.

Advantages

- Improved starting in below zero and wet conditions
- Recommended for all gas and diesel powered vehicles with fuel injection systems
- Suitable for recreational vehicles: powerboats, snowmobiles, etc.

Application

- Treatment ratio is 150ml for ever 24-35L of fuel
- Heavy duty or severe applications may require increased treatment ratio
- Industrial grade; do NOT use for food-grade applications
- Industrial Grade: do NOT use for Hand Sanitizer, can be used for industrial sanitizing purposes.
- Isopropyl is highly flammable; follow safe handling procedures. Keep away from sources of heat, hot surfaces, sparks, open flames, and other ignition sources.

Use and Storage

Always read and follow your vehicle manufacturer's winterizing instructions. Isopropyl has a shelf life of 3 years under ideal storage conditions. Keep packages closed while not in use, store in a cool, dry area and away from open heat sources, sparking tools and equipment.

Health, Safety, & Environment

GHS compliant Safety Data Sheets are available at nemco.ca under the Safety Data Sheets. For SDS in French, please contact info@nemco.ca. This material is WHMIS 2015 and TDG classified. The SDS contains valuable information critical to the safe handling and proper use of the product. Always take used chemicals to an authorized collection point. Avoid discharge into drains, soil, or water. As with any chemical, keep out of reach of children and animals.

Quality

Nemco works with respected industry suppliers. Nemco Resources Limited manufacturing facility in Winnipeg, Manitoba is proud to be certified to ISO9001. For questions regarding quality, please contact your local sales representative.

Typical Characteristics - Isopropyl Fuel De-Icer

Properties	Method	Performance	Properties	Method	Performance
Colour	Appearance	Colourless	Freeze point, °C(°F)	ASTM D3321	-88(-126)
SPG, 15.6°C	Internal	0.790	Flash point, °C(°F)	ASTM D56	12(54)

These characteristics are typical of current production, variations in these characteristics may occur.

Availability and product codes

Pack size	12x350ml	20L pail	205L drum			
Fuel Injector Cleaner	CHCPZ0004	CHCPZ0041	Special Order			
Availability	To order, contact us toll free 855-755-6737 or at orderdesk@nemco.ca					

Isopropyl Fuel De-Icer Issue Date: 12/18/15 Revision Date: 08/11/21 Rev#: 1.1 Page 1 of 1