

Premium Snowblower Oil Synthetic Blend 5W-30 Motor Oil

Description

Nemco Premium Snowblower Oil is a Synthetic Blend Motor Oil designed for use in gasoline powered snow machines. Premium Snowblower Oil is formulated with a selected combination of high quality, high viscosity index mineral and synthetic base oils, and has a proven additive systems with the proper balance of detergents, dispersants, rust and high temperature oxidation inhibitors along with exceptional anti-wear protection.

Nemco Premium Snowblower Oil is an SAE 5W-30 multi-grade motor oil that is an approved API Service SP and ILSAC GF-6A engine oil providing significant performance enhancements in deposit control, volatility control, and fuel economy.

Advantages

- Multi-grade properties of SAE 5W-30 to provide ease of starting in cold conditions.
- Improved volatility control reducing oil consumption.
- Quality balanced formula promotes engine cleanliness and helps extend engine life.
- Enhanced deposit control reduces wear, protecting highly loaded engine parts

- Excellent oxidation protection for high temperatures experienced by modern snow machines
- Synthetic blend formula provides easier cold-temperature starting

Application

- Gasoline powered snow machines

Meets/Exceeds

- Approved API Service SP / ILSAC GF-6A
- API Resource Conserving properties

Suitable/Recommended for

- Suitable for use in older equipment calling for API SN, SM / ILSAC GF-5 qualified oils

Use and Storage

To get the best performance from your equipment ensure products meet or exceed manufacturing requirements. Lubricants typically have a shelf life of 5 years under ideal storage conditions. Keep containers in good condition and away from moisture. Keep closures securely in place to prevent exposure to air which may cause the product to dry out. Where possible, avoid storage in areas where the temperature fluctuates between extreme highs and lows.

Typical Characteristics - Premium Snowblower Oil

Properties	Method	Result
Oil Type / SAE	-	Synblend 5W-30
API Service Cat.	-	SP / ILSAC GF-6A
Flash Point °C (°F)	ASTM D92	220(429)
Pour point °C (°F)	ASTM D97	-43 (-45)
Kinematic Vis @40°C mm²/s	ASTM D445	61
Kinematic Vis @100°C mm²/s	ASTM D445	10.5
Viscosity Index	ASTM D2270	162
CCS Viscosity @°C	ASTM D5293	6000 @ -30

These characteristics are typical of current production, variations in these characteristics may occur.

Availability and product codes

Pack size	12x1L case	4x5L case
Premium Snowblower Oil	GMORZ0075	Special Order
Availability	To order, contact us toll free at 855.755.6737 or orderdesk@nemco.ca	

Health, Safety, & Environment

GHS compliant Safety Data Sheets are available at nemco.ca under 'Safety Data Sheets'. For SDS in French, please contact info@nemco.ca. This material is classified under WHMIS 2015. Please refer to the SDS which contains valuable information critical to the safe handling and proper use of the product. Always take used grease to an authorized collection point. Avoid discharge into the environment. As with any lubricant, keep out of reach of children and animals.

Quality

Nemco works with respected industry suppliers and is an active member of ILMA. Nemco Resources Limited manufacturing facility in Winnipeg, Manitoba is proud to be certified to ISO 9001. For questions regarding quality, please contact our Technical Sales Representative.