

PRODUCT DATA SHEET

Rustillo

Low Viscosity Preservative Oil

Description

Nemco Rustillo is a low viscosity preservative oil formulated by using a high quality petroleum solvent and Group II base oils, and an additive package that provides this low viscosity oil with anti-rust, anti-corrosion and anti-wear properties. The anti-corrosion properties of this oil provide protection for your equipment or container between operations and in storage. As the solvent evaporates, the very thin residual film provides effective protection against corrosion and suppresses any corrosive attack resulting from fingerprints on the components.

Advantages

- Excellent corrosion protection
- Low viscosity, easy spray application
- Economical, good value
- Low pour point, excellent for cold winter protection

Applications

- High speed machine tool spindles and hydraulic applications
- Ideal medium for cooling and flushing applications in lower temperature
- Equipment or containers going into storage and requiring anti-corrosion and anti-rust protection
- Rustillo contains solvent and is a flammable liquid and vapour. Keep product and containers away from sources of ignition.

Use and Storage

To get the best performance from your equipment ensure products meet or exceed manufacturing requirements. Lubricants typically have a shelf life of 5 years under ideal storage conditions. Keep drums and totes in good condition and away from moisture. Keep bungs securely in place; as bungs breath moisture can seep in over time. Where possible, avoid storage in areas where the temperature fluctuates between extreme highs and lows.

Typical Characteristics - Rustillo

Properties	Method	Result
Kinematic Vis@40°C mm²/s	ASTM D445	2 - 2.5
SPG, 15.6°C	Internal	0.8171
Freeze point, °C(°F)	ASTM D3321	-40(-40)
Flash point, CC °C(°F)	ASTM D56	46(115)

These characteristics are typical of current production, variations in these characteristics may occur.

Rustillo Issue Date: 2011 Revision Date: 08/24/21 Rev#: 2 Page 1 of 2

Availability and product codes

Pack size	20L pail	1,000 tote/Bulk
Rustillo	IOORZ0054	IOORZ0081
Availability	To order, contact us toll free 855-755-6737 or at orderdesk@nemco.ca	

Health, Safety, & Environment

NEMCO

GHS compliant Safety Data Sheets are available at nemco.ca under Safety Data Sheets. For SDS in French, please contact info@nemco.ca. This product is WHMIS 2015 and TDG classified. The SDS contains valuable information critical to the safe handling and proper use of the product. Always take used oil/chemical to an authorized collection point. Do not discharge into drains, soil, or water. As with any chemical, keep product out of reach of children and animals.

Quality

Nemco Resources Ltd works with respected industry suppliers for lubricant additives and base oils. Nemco is a member of ILMA and the manufacturing facility in Winnipeg, Manitoba is proud to be certified to ISO9001. For questions regarding quality, please contact your Technical Sales Representative.

Rustillo Issue Date: 2011 Revision Date: 08/24/21 Rev#: 2 Page 2 of 2